

Cable Support Systems are well designed to provide necessary support for cable trays, cable ladders and trunkings. Cable supports are manufactured according to common standards from high quality ...

The load capacity of the cable trays according to the support width can be read off in the diagram using load curves - here, shown as an example for a cable tray with the tray widths 100 to 600 mm.

These supports offer a robust and stable base for the trays and are designed to support heavy loads. Additionally, they provide an elevated solution that prevents damage to cables due to moisture or ...

The various series of support elements, even if not all of them, are conceived to be installed on all the three canonical axes: X, Y and Z. The bolted structures, thanks to their modularity, can be easily put ...

Contact us today for your custom or standard sized support bracket needs. Supports should be located so that connectors (splice joints) between horizontal runs fall between the support point and quarter ...

Calculation modules on-line for simulation of the load, cable filling or other parameters of cable route size to facilitate selection of the most appropriate products.

Hemming is a part of most semi-finished products to create cable tracks. It strengthens the structure, ensures safe routing of cable installations and prevents from damage by sharp edges.

Stainless steel Zinc Zinc cable tray and stainless steel accessory Galvanic corrosion must be taken into account within the whole cable management system and makes it essential to choose the right ...

The system consists of a vertical tray and support beds. The tray is anchored to the load-bearing structure from below using stainless steel anchors. Standard products use the following beam types: ...

KBS cable trays have embedded perforations for added load-bearing capacity, better cooling, stability and condensation drainage. Longitudinal and transverse perforations provide better fastening to the ...

Web: <https://www.prospettivacasa.eu>

