

ST7789V TFT Controller Datasheet. This document is a datasheet that describes the ST7789V, a single-chip TFT controller/driver with a 240RGB x 320 dot 262K color display and frame memory.

Dual-MCU board combining RP2040 and ESP32-C3, with a 1.14-inch ST7789V display, WiFi, BLE 5.0, and Arduino/MicroPython support -- bringing Raspberry Pi Pico connectivity to wireless IoT projects.

This IPS display features a 2-inch diagonal with 240x320 resolution and an embedded controller, communicating via SPI interface. The module requires minimum GPIO for controlling and ...

The ST7789V is a single-chip controller/driver for 262K-color, graphic type TFT-LCD. It consists of 720 source line and 320 gate line driving circuits. This chip is capable of connecting directly to an ...

To use this module, you will need a screen using the ST7789V controller and a device with GPIO pins and an SPI bus (or implementation) which can run Python 3. This was developed using a ...

This 2 inch LCD display offers a SPI interface and resolution of 320 x 240, based on a built-in ST7789V controller, providing Raspberry Pi (C and Python), Arduino, Raspberry Pi Pico and ESP32 demo codes.

Selection Datasheet search, datasheets, Datasheet search site for Electronic Components and Semiconductors, integrated circuits, diodes, triacs and other semiconductors.

The board features a 2.8-inch TFT LCD driven by the ST7789V controller with a resolution of 320 x 240 pixels (QVGA) and support for 65K colors. It connects via an SPI interface.



ST7789V Hardware Interface

Web: <https://www.prospettivacasa.eu>

