

Switch Aggregation and Uplink Mode

The regular Aggregation switch is best used to connect all devices in a rack together when there is no need for an "even bigger pipe". So for SMBs or Prosumers that need a 10Gbps backbone but ...

Port aggregation can increase maximum throughput, and allow for network redundancy. It does this by splitting traffic across multiple ports instead of forcing clients to use a single uplink port on a switch.

Even though there are two or more paths between the two switches, each individual data flow can only use one path in order to maintain proper data sequencing. A data flow will failover almost instantly to ...

Configuring port aggregation on a UniFi switch is straightforward using the UniFi Network Controller (or UniFi OS Console). The process involves selecting the ports you wish to combine, ...

Troubleshooting: When LACP (Link Aggregation Control Protocol) or static LAG (Link Aggregation Group) is not functioning properly, common troubleshooting steps and checkpoints ...

Port aggregation is useful for implementing load balancing and provides a redundant link backup. To allow port aggregation, the basic configuration on all the ports must be consistent. The following list ...

Configure link redundancy in network topologies with dual uplink between different layers of the network. Configure UFD to achieve network path redundancy. Applicable products, versions, ports and ...

Aggregating multiple links between physical interfaces creates a single logical point-to-point trunk link or a LAG. The LAG balances traffic across the member links within an aggregated Ethernet bundle and ...

The Add link aggregation link will no longer be available once the maximum number of link aggregation groups are configured on the stack. Link aggregation to an uplink switch from two members in a ...

Web: <https://www.prospettivacasa.eu>

